



Technical Specifications	Parquet Collection	Hardwood Collection
Width	90 mm / 125 mm / 148 mm / 189 mm	8 <mark>3 mm / 90 mm /</mark> 125 mm / 148 mm
length	600 - 1800 mm	300 mm - 1800 mm
Box per Sqm.	2.15	2.1 m ²
Thickness	14 mm / 15 mm	15 mm / 18 mm / 20 mm / 22 mm
Wear Layer	3 mm / 4 mm / 5 mm	
Composition	1 strip / 3 ply	
Planks / Box	6 (2,11 m²)	
Box / Pallet	50 (105, 5 m²), 60 (126, 6 m²)	104.05 m²
Pallets / 20' Ctr	(6 x 50) + (6 x 60), 1392, 60 m²	10 pallets
Pallets / 40' Ctr	(12 x 50) + (12 x 60), 2785, 20 m²	18 pallets
Bevels	Micro bevel	Micro bevel
Waste	A \pm 5% margin for error accepted as per industry standard	A \pm 5% margin for error and imperfection is an accepted industry standard.
Moisture	Content between 6% to 8%	Content between 6% to 8%
Recommended Relative Humidity	37% to 60%	37% to 45%
Finish	7 layers of UV matt lacquer, 7 layers of UV Oil, White Oil	7 layers of scratch resistance lacquer, 7 layers of UV Oil, White Oil
Installation	Nail down, Glue down, Floating method	Nail down and Floating Method
Warranty	10 years against all manufacturing defects; see warranty leaflet	10 years against all manufacturing defects; see warranty leaflet
Wrapping	Polystyrene membrane	Polystyrene membrane
Grains (cuts)	Plain Sawn, Rift Sawn	Plains Sawn
Grades	Premier: Knots free, variation in colour from brown to clear. Second and Better: Mixture of Premier and Natural grades Natural: Variation in colouring from very dark to light tones. Mineral streaks accepted.	Premier: Knots free, variation in color from brown to clear. Second and Better: Mixture of Premier and Natural grades. Natural: Variation in coloring from vey dark to light tones. Minerals Streaks accepted. Sound knots accepted





CANQUEST FLOORING Sales Office:

Canquest Hardwood Flooring 4 Robert Speck Parkway, Suite 1500 Mississauga, Ontario L4Z 151 Phone: +(905) 402-3224





